

T5000 Marine Acoustic Hood



Environment

For external or internal use, the T5000 Marine is designed for harsh and noisy environments attaining a high level of noise reduction up to 23.9 dB.

The T5000 Marine is extremely robust and weatherproof and manufactured using high quality, long lasting components.

Manufacturing

Thermoset composite GRP moulding manufactured using a certified RTM system to BS476 Part 7 Class II surface spread of flame.

Inside the hood's outer shell is a perforated 3mm polypropylene lining that houses 60mm non-hygroscopic, high performance acoustic insulation.

Fitted to the inner back wall is a stainless steel apparatus plate with a white powder coat finish; beneath this is a 316 powder coated stainless steel shelf with easy cable entry.





T5000 Marine Acoustic Hood

Specifications*

- Outer Shell Thermoset composite GRP moulding Manufactured using a certified RTM system to BS476 Part 7 Class II surface spread of flame.
- Acoustic Insulation 60mm Tissue faced non hygroscopic Rockwool (RW3) density 60kg/m3
- Insulation Liner White Perforated Polypropylene 3mm thickness. UL94 HB
- Apparatus plate 316 Grade Stainless Steel, 2mm thickness, powder coated white
- Mounting Brackets 316 Stainless Steel, 6mm thickness
- 316 Stainless Steel Shelf, powder coated white
- Bolts, nuts and washers A4 stainless steel
- Majority of assembly rivets A4 stainless steel

Colours Available**



Dimensions

- Product size H920mm W700mm D610mm
- Product weight approx 31.5kg
- Boxed size 980 x 800 x 680mm
- Boxed weight Approx 37kg

*Our products are subject to a continuous improvement process and specifications may change without notice. Please check specifications are current at time of placing order.

**Component colours may be subject to slight variations through pigmentation changes and batch runs. Please notify the sales team in advance of any concerns.

***Telephones are for illustrative purposes only and are not included.